

**PAT-NO:** JP410273559A  
**DOCUMENT-IDENTIFIER:** JP 10273559 A  
**TITLE:** RUBBER COMPOSITION FOR  
TIRE TREAD IMPROVED IN  
PROCESSIBILITY  
**PUBN-DATE:** October 13, 1998

**INVENTOR-INFORMATION:**

NAME	COUNTRY
ISHIKAWA, KAZUNORI	
YATSUYANAGI, CHIKASHI	

**ASSIGNEE-INFORMATION:**

NAME	COUNTRY
YOKOHAMA RUBBER CO LTD:THE	N/A

**APPL-NO:** JP10015735  
**APPL-DATE:** January 28, 1998

**INT-CL (IPC):** C08L009/00 , B60C001/00 , B60C011/00 ,  
C08K003/36 , C08K005/54

**ABSTRACT:**

**PROBLEM TO BE SOLVED:** To improve the processibility of a silica-loaded vulcanizable rubber compsn. without detriment to the characteristics inherent in the compsn., such as low heat build-up properties and abrasion resistance, by compounding a diene rubber with silica and a polysiloxane obtd. by the condensation of an alkoxy silane contg. at least one compd. selected from among five compds.

**SOLUTION:** This compsn. contains 100 pts.wt. diene rubber, 5-80 pts.wt. silica, and a polysiloxane obtd. by the condensation of an alkoxysilane contg. at least 60 wt.% at least one compd. selected from among compds. represented by formulas I to IV (wherein R1 is methyl or ethyl; Me is methyl; and Ph is phenyl). When not only alkoxysilyl groups which bond to silanol groups present on the surface of silica but also functional groups which chemically bond to a rubber are bonded to the polysiloxane in advance, more effective bonding between a rubber and silica is achieved. The polysiloxane used essentially has alkoxysilyl groups and hydrophobic groups.

**COPYRIGHT:** (C)1998,JPO